



PROJECT: _____
 ITEM # _____ QTY: _____
 MODEL # _____
 AIA # _____ SIS # _____

VICTORY ELITE™ TOP MOUNT REFRIGERATOR

VICTORY ELITE™ TOP MOUNT REFRIGERATOR

VERSA-3D-SD-HC



CABINET CONSTRUCTION

- Stainless Steel Front, Aluminum Interior
- Snap-in, Magnetic Door Gasket(s) With A 2 Year Warranty
- Heavy Duty Cam Lift Hinges With Lifetime Warranty
- Features Stay-Open Door For Easy Product Loading
- Required Clearance Is 12" Top, 3" Rear And 0" Sides
- Field Reversible Doors
- 6" Casters
- 8' Cord and Plug

FEATURES

- High Performance Refrigeration System With An Electronic Control
- Energy Efficient LED Lighting
- Heavy Duty Epoxy Coated Shelves

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Hot Gas Condensate Evaporator
- Automatic, Non-Electric Defrost
- Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Refrigerator Capable Of Maintaining Product Temperature Between 36°F And 38°F



Please verify qualifying units by visiting:
www.energystar.gov/cfs

- ▶ 3 Year Parts & Labor Warranty
- ▶ Plus An Additional 2 Year Compressor Warranty
- ▶ Exclusive 2 Year Warranty On Magnetic Door Gaskets
- ▶ Lifetime Warranty On Handles & Hinges (Parts Only)

OPTIONS & ACCESSORIES

- Stainless Steel Back
- 6" Legs Or 3" Casters (No charge at time of unit order)
- Additional Shelves: Heavy Duty Epoxy Coated, Chrome Plated Or Stainless Steel
- Stainless Steel Breaker
- Seismic/Flanged Legs
- Remote Models* (6" Legs Only) (Refrigerant must be specified at time of order, see note on back page)
- Tray Slides

3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com


Rev. 09/19/19 Printed in U.S.A.

APPROVAL: _____ DATE: _____



VICTORY ELITE™ TOP MOUNT REFRIGERATOR

VERSA-3D-SD-HC



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	71.52	Cabinet Voltage	115/60/1	Height	88"
Width, Overall (in.)	78"	Total Amperes	6.0	Width	80"
Depth, Overall (With Handle)	33 7/8"	NEMA Plug* (8' cord)	5-15P	Depth	36"
Height Overall (6" Casters)	84 3/4"	REFRIGERATION DATA		Created Weight	720 lbs
Depth, Door Open 90°	55 1/8"	Condensing Unit Size, HP*	Variable Speed Technology	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified at time of order.	
Door Opening (in.)	21 5/8" x 61 3/4"	Refrigerant*	R290		
No. Of Doors/Shelves	3/9	Capacity (BTU/HR) (100°F/20°F)	Variable Speed Technology		

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com

Rev. 09/19/19 Printed in U.S.A.

an Ali Group Company



The Spirit of Excellence