

UNDERCOUNTER SIDE-MOUNT REFRIGERATORS

VUR93HC

- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

VICTORY

ULTRASPEC®

STANDARD FEATURES

- Full Electronic Control
- Stainless Steel Exterior/Aluminum Interior
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- Cartridge Style Hinges
- 1/2" Thick Durable Sub Top
- Self-Closing Doors with 120° Stay-Open Feature
- (2) Epoxy Coated Shelves Per Door Section
- 6" Casters, 2 with Brakes
- 10' Cord & Plug



VUR93HC

OPTIONS & ACCESSORIES

- 3" ADA Casters
- 6" Legs or 6" Seismic Legs
- Richlite Cutting Board
- Overshelves
- Stainless Steel Interior
- LED Lighting
- Secure-Temp 1.0™ Technology
- 220/50 Hz, 220/60Hz Voltages
- Remote Models
- Change Door Swing - at time of order
- Extra Shelves
- Epoxy, Chrome Plated, or Stainless Steel
- Gasket Guards
- Stainless Steel Back
- Door Locks



3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

CABINET CONSTRUCTION

Construction features include stainless steel exteriors and aluminum interiors. Cabinet back and bottom are galvanized steel. Interiors accommodate sheet pans and hotel pans.

Cabinets are insulated with 2" thick foamed-in-place polyurethane insulation. Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. Doors are equipped with a snap-in-place vinyl magnetic gaskets for positive seal. Convenient, double pull style door handle. 6" high casters are standard, 2 include brakes. An 10' cord set is provided with 115 volt models. Cabinet interior standard with 2 steel wire epoxy coated shelves per section.

REFRIGERATION SYSTEM

Forced air refrigeration systems use a cap tube to meter refrigerant. Automatic electric defrost is standard. Automatic (non-electric) condensate evaporator is provided.

Refrigerants include CFC free R-290 in refrigerator to comply with all environmental standards.

CHARACTERISTICS	VUR93
Net Capacity (cu. ft.)	29.7
Width, Overall (in.)	93"
Depth, Overall	35.75
Depth, Door(s) Open 90°	57"
Height Overall	34.5
No. of Doors	3
No. of Shelves	6

ELECTRICAL DATA

Condensing Unit Voltage	115/60/1
Total Amperes	4.9

NOTE: Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

REFRIGERATION DATA

Condensing Unit Size	1/3 HP
Refrigerant	R-290

CRATED WEIGHT

495 LBS

* Remote units use R-404A refrigerant standard and come with 6" legs

