

**UNDERCOUNTER
SIDE-MOUNT
REFRIGERATORS
WITH DRAWERS**

VURD119HC-2

- 3 Year Parts & Labor Warranty Plus an Additional
2 Year Compressor Warranty

- Exclusive 2 Year Warranty on Santoprene Door Gaskets

VICTORY
ULTRASPEC®

STANDARD FEATURES

- Full Electronic Control
- High Performance, Balanced, Bottom-Mounted Refrigeration
- Anti-Corrosion Coated Evaporator Coil
- Stainless Steel Exterior / Aluminum Interior
- Cabinet back and bottom galvanized steel
- Environmentally Safe R290 Refrigerant For Freezers
- 2" Thick Foamed-in-Place Polyurethane Insulation
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- Self-Closing Door(s) with 120° Stay-Open Feature
- Cartridge Style Hinges
- 2 Epoxy Coated Shelves per Door Section
- Telescoping drawers slides
- Slides include locking mechanism to prevent drawers from being pulled off of cabinets
- Upper drawers accommodates 6" deep foodservice pans
(pans not included)
- Lower drawers accommodates 6" deep foodservice pans
(pans not included)
- 6" Casters Standard, 2 with Brakes
- 10' Cord and Plug (see electrical data for details)



VURD119HC-2

OPTIONS & ACCESSORIES

- Change Door Swing
- 220/50 Hz, 220/60Hz Voltages
- 3" Overall Height Casters (Set of 4)
- Extra Shelves
- Secure-Temp 1.0™ Technology



3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

CABINET CONSTRUCTION

Heavy duty construction includes exterior stainless steel on front, sides, doors and grille. Cabinet back and bottom are galvanized steel. Interior liner is made of corrosion resistant aluminum. Interior thermometer is standard.

Cabinet is insulated with 2" thick foamed-in-place polyurethane insulation. Sub-top insulated with 1-1/2" foamed-in-place polyurethane insulation. Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. Doors are equipped with a snap-in-place vinyl magnetic gasket for positive seal. 6" high casters are standard, 2 include brakes. An 8' cord set is provided with 115 volt models. Cabinet interior standard with 2 steel wire epoxy coated shelves per section.

DRAWER CONSTRUCTION

Drawer frames are constructed of heavy-duty stainless steel and are supported on heavy-duty telescoping drawer slides for maximum support of stored food products. Slides have locking mechanism to prevent from drawers being pulled off of cabinets. Upper pull-out drawers accommodate 6" deep pans. Lower pull-out drawers accommodate two 6" deep pans. Heavy-duty pan divider supports are supplied. Foodservice pans for drawers are not included. Snap-type vinyl magnetic gasket is attached to each drawer for positive seal.

ELECTRONIC CONTROL

REFRIGERATION SYSTEM

Forced air refrigeration systems use expansion valve to meter refrigerant. Automatic electric defrost is standard. Automatic (non-electric) condensate evaporator is provided.

Refrigerators operate at 36° - 38°F

CHARACTERISTICS	VURD119HC-2
Net Capacity (cu. ft.)	52.5
Width, Overall (in.)	119"
Depth, Overall	35.75
Depth, Door(s) Open 90°	57 1/16"
Height Overall	34 1/2"
No. Doors/Drawers	3/2
No. of Shelves	6

ELECTRICAL DATA	
Condensing Unit Voltage	115/60/1
Total Amperes	4.9

NOTE: Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

REFRIGERATION DATA	
Condensing Unit Size	1/3 HP
Refrigerant	R-290

CRATED WEIGHT	535 LBS
---------------	---------

* Remote units use R-404A refrigerant standard and come with 6" legs

